

SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Material name Husqvarna 2-Stroke Oil Guard

Recommended use 2-Stroke oil.

Version No. 01 CAS No. Mixture

Product code 544 97 65-01 (1L), 544 97 65-02 (0,1L)

Manufacturer

Supplier Husqvarna New Zealand Ltd

Address 51 Aintree Avenue, Mangere, Auckland 2022

Country New Zealand Telephone +64 9 920 2410 e-mail

anthony.barry@husqvarnagroup.com Contact Anthony Barry

Emergency Contact the Poisons Information Centre; Ph. 0800 764 766

2. HAZARDS IDENTIFICATION

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. Material is not hazardous as defined by the Approved Criteria for Classifying Hazardous Substances NOHSC:1008.

Risk phrase(s) None Safety phrase(s) None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS No.	Percent
Highly refined mineral oil (DMSO-extract < 3% IP 346)	- -	> 60
Distillates (petroleum), hydrotreated light	64742-47-8	10 - < 30
Hydrocarbyl amine	Polymer	< 10

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

4. FIRST-AID MEASURES

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Call a physician if symptoms develop or

Skin contact Wash with soap and water. In case of rashes, wounds or other skin disorders: Seek medical

attention and bring along these instructions. If high pressure injection under the skin occurs,

always seek medical attention.

Eye contact Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open

eyelids wide apart. Get medical attention if irritation develops or persists.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get immediate

medical attention.

General advice Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

Notes to physician Provide general supportive measures and treat symptomatically. Droplets of the product aspirated

into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Symptoms may be delayed. HIGH PRESSURE SKIN INJECTION: Physician must be familiar with local procedures for treatment of this type of wound; incision, irrigation, removal of all necrotic tissue

and open wound dressing.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Foam. Dry powder. Carbon dioxide (CO2). Water fog.

Extinguishing media which must not be used for safety Do not use water jet as an extinguisher, as this will spread the fire.

reasons

Unusual fire & explosion Heating will generate vapours which may form explosive vapour/air mixtures. Material will float and

hazards can be re-ignited on surface of water.

Husqvarna 2-Stroke Oil Guard MSDS Australia 906396 Version No.: 01 Revision date: -Issue date: 15-November-2013

Specific hazards By heating and fire, irritating vapours/gases may be formed.

Special protective equipment

for fire-fighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in

the workplace.

Specific methods Move containers from fire area if you can do so without risk. Use water spray to cool unopened

containers. Cool containers exposed to flames with water until well after the fire is out.

Hazchem Code None

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). In case of

spills, beware of slippery floors and surfaces. Avoid breathing mist or vapour. Avoid contact with skin and eyes. Wear protective clothing as described in section 8 of this safety data sheet.

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not allow to enter drains, sewers or

watercourses. Environmental manager must be informed of all major releases.

Containment procedures Remove sources of ignition. Stop the flow of material, if this is without risk. Dike the spilled

material, where this is possible.

Methods for cleaning up Large Spills: Use a non-combustible material like vermiculite, sand or earth to soak up the product

and place into a container for later disposal. Wash area with soap and water.

Small Spills: Absorb spillage with non-combustible, absorbent material. Clean surface thoroughly

to remove residual contamination.

Never return spills in original containers for re-use. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Handling Use only in well-ventilated areas. Avoid inhalation of oil mist and contact with skin and eyes. Wear

protective clothing as described in Section 8 of this safety data sheet. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using the product. Be aware of potential for

surfaces to become slippery. Observe good industrial hygiene practices.

Storage Keep away from ignition, flame and heat sources. Store in a cool, dry, well-ventilated place. Store

away from incompatible materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form	
OIL MIST (MINERAL) (CAS	TWA	5 mg/m3	Inhalable fraction.	
-)				

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)

Components Type Value

OIL MIST (MINERAL) (CASTWA5 mg/m3

-)

Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment)

Components	Туре	Value	Form	
OIL MIST (MINERAL) (CAS	TWA	5 mg/m3	Mist.	90
-)				

Recommended monitoring procedures

Additional exposure dataFollow standard monitoring procedures.

Engineering measures Provide adequate ventilation and minimise the risk of inhalation of vapours and oil mist. Use

explosion-proof equipment. Provide easy access to water supply and eye wash facilities.

Personal protective equipment

Respiratory protection In case of inadequate ventilation or risk of inhalation of oil mist, suitable respiratory equipment with

particulate filter and organic vapor cartridges can be used. Wear air-supplied mask in confined

areas. Seek advice from local supervisor.

Hand protection Wear protective gloves. Nitrile gloves are recommended, but be aware that the liquid may

penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the

glove supplier.

Eye protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear appropriate clothing to prevent repeated or prolonged skin contact.

Environmental exposure

controls

Environmental manager must be informed of all major spillages.

Husqvarna 2-Stroke Oil Guard 906396 Version No.: 01 Revision date: -

MSDS Australia

Issue date: 15-November-2013

Hygiene measures

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using, do not eat, drink or smoke. Launder contaminated clothing before reuse. Private clothes and working clothes should be kept separately.

9. PHYSICAL AND CHEMICAL PROPERTIES

AppearanceBlue liquid.Physical stateLiquid.FormLiquid.ColourBlue.

Odour Organic solvents.
Odour threshold Not available.

PH Not available.
Vapour pressure Not available.
Vapour density Not available.

Boiling point Not available.

Melting point/freezing point Not available.

Solubility (water) Negligible.

Flash point > 75.0 °C (> 167.0 °F)

Flammability limits in air, upper, % by volume

Not available.

Flammability limits in air, lower, % by volume

Not available.

Auto-ignition temperature Not available.

Evaporation rate Not available.

Viscosity 45 mm2/s (approximate) (40 °C)

Other data

Explosive properties Not available.

Flammability (solid, gas) Not applicable.

Oxidizing properties Not oxidizing.

Relative density 0.871 (approximate) (15 °C)

10. STABILITY AND REACTIVITY

Conditions to avoid Heat, sparks, flames, elevated temperatures. Contact with incompatible materials.

Materials to avoid Strong oxidising agents. Strong acids.

Hazardous decomposition

products

By heating and fire, irritating vapours/gases may be formed. Carbon oxides.

Hazardous polymerisation Hazardous polymerisation does not occur.

11. TOXICOLOGICAL INFORMATION

Acute toxicity May irritate and cause stomach pain, vomiting, diarrhoea and nausea. Human evidence indicates

that the product has very low acute oral, dermal or inhalation toxicity. However, it can produce severe injury if taken into the lung as a liquid, and there may be profound central nervous system

depression following prolonged exposure to high levels of vapour.

Routes of exposure Eye contact. Ingestion. Inhalation. Skin contact.

Chronic toxicity Prolonged contact may cause dryness of the skin. Prolonged or repeated inhalation may cause

respiratory tract irritation.

SensitisationNo data available.CarcinogenicityNot classified.

Mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

TeratogenicityNo data available. **Reproductivity**No data available.

Symptoms and target organs May cause eye irritation on direct contact. Defatting of the skin. Dermatitis. Ingestion may cause

irritation and malaise. In high concentrations, mists/vapors may irritate throat and respiratory

system and cause coughing.

Prolonged and repeated contact with used oil may cause serious skin diseases, such as **Further information**

dermatitis and skin cancer.

12. ECOLOGICAL INFORMATION

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability Expected to biodegrade slowly.

Mobility The product is insoluble in water. It will spread on the water surface while some of the components

will eventually sediment in water systems. The volatile components of the product will spread in the

atmosphere. The product adsorbs strongly to soil.

Bioaccumulation The product contains potentially bioaccumulating substances.

Other adverse effects Oil spills are generally hazardous to the environment.

13. DISPOSAL CONSIDERATIONS

Disposal instructions Dispose in accordance with all applicable regulations. This material and/or its container must be

disposed of as hazardous waste.

Waste from residues / unused

products

Dispose of in accordance with local regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Hazchem Code None

15. REGULATORY INFORMATION

National regulations This Material Safety Data Sheet was prepared in accordance with the Australia National Code of

Practice for the Preparation of Material Safety Data Sheets (NOHSC: 2011.)

Listed.

Australia HVIC: Listed substance

Distillates (petroleum), hydrotreated light (CAS

64742-47-8)

Highly refined mineral oil (DMSO-extract < 3% IP 346)

Listed (CAS -)

16. OTHER INFORMATION

Recommended use 2-Stroke oil.

Recommended restrictions Use in accordance with supplier's recommendations.

Bibliography HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

available.

Prepared by Husqvarna AB Issue date 15-November-2013

Revision date

MSDS Australia Issue date: 15-November-2013