

Engine Specifications	
Model	GS190A
Type	4-stroke, OHC, single cylinder
Displacement	187 cm ³ (11.4 cu-in)
Max. horsepower	6.0 HP (4.4 kW) at 3,600 rpm
Max. torque (crank PTO)	12.1 N·m (1.23 kg·m, 8.9 ft·lb) at 2,500 rpm
Carburetor	Horizontal type, butterfly valve
Cooling system	Forced-air
Ignition system	Transistorized magneto ignition
Lubricating system	Splash
Starting system	Recoil starter
Stopping system	Ignition primary circuit ground
Fuel used	Unleaded gasoline (octane number 86 or higher)
Fuel tank capacity	2.0 l (0.5 US.gal, 0.4 Imp. gal)
Fuel consumption	230 g/HPh
PTO shaft rotation	Counterclockwise (from PTO shaft side)

DIMENSIONS AND WEIGHT	
Length, mm (in)	345 (13.6)
Width, mm (in)	369 (14.5)
Height, mm (in)	343 (13.5)
Dry weight, kg (lb)	13.8 (30.4)
Operating weight, kg (lb)	15.8 (34.8)

CYLINDER BLOCK AND HEAD	
Compression ratio	8.5:1
Bore x Stroke	69 mm X 50 mm (2.71 x 1.97 in)
Sleeve internal diameter	69.00 mm (2.7165 in)
Piston skirt outer diameter	68.985 mm (2.7159 in)
Number of piston rings (compression / oil)	2 / 1
Ring side clearance (Top/Second/Oil)	0.035-0.065 mm (0.0013-0.0026 in) / 0.015-0.049 mm (0.0006-0.0019 in) / 0.15-0.35 mm (0.006-0.014 in)
Ring end gap (Top/Second/Oil)	0.20-0.35 mm (0.008-0.014 in) / 0.30-0.45 mm (0.012-0.018 in) / 0.15-0.35 mm (0.006-0.014 in)
Ring width (Top/Second/Oil)	1.5 mm (0.06 in) / 1.5 mm (0.06 in) / 2.5 mm (0.10 in)
Connecting rod small end ID	13.005 mm (0.512 in)
Connecting rod big end ID	30.02 mm (1.1819 in)

Crankpin outer diameter	29.980 mm (1.1803 in)
Main journal outer diameter	PTO side: 27.993 mm (1.1021 in), Flywheel side: 25.393 mm (0.9997 in)

Cylinder Head	
Warpage (limit)	0.10 mm (0.004 in)
Valve Arrangement	OHC
Valves	2
Stem outer diameter (standard)	INTAKE: 5.480 mm (0.216 in), EXHAUST: 5.44 mm (0.214 in)
Guide internal diameter (INTAKE/EXHAUST)	5.5 mm (0.2165 in)
Spring free length	34.0 mm (1.34 in)

Tightening Torque Specs	
Crankcase cover	12 Nm; 1.2 kg·m; 8.6 ft·lb
Connecting rod bolt	12 Nm; 1.2 kg·m; 8.6 ft·lb
Valve adjusting lock nut	8 Nm; 0.8 kg·m; 5.8 ft·lb
Cylinder head cover bolt	12 Nm; 1.2 kg·m; 8.6 ft·lb
Oil drain plug bolt	24 Nm; 2.4 kg·m; 17 ft·lb
Flywheel nut	75 Nm; 7.6 kg·m; 55 ft·lb
Governor arm nut	10 Nm; 1.0 kg·m; 7 ft·lb
Muffler bolt	12 Nm; 1.2 kg·m; 8.6 ft·lb

Recoil starter nut	8.5 Nm; 0.85 kg·m; 6.1 ft·lb
Fan cover stud bolt	12 Nm; 1.2 kg·m; 8.6 ft·lb
Spark plug	20 Nm; 2.0 kg·m; 14 ft·lb

Service Information	
Maximum speed	3,850 ± 150 rpm
Idle speed	1,400 ± 150 rpm
Cylinder compression	5.0 kg/cm ² (71 psi) at 600 rpm
Valve clearance	Intake valve: 0.15 ± 0.04 mm (0.006 ± 0.002 in), Exhaust valve: 0.20 ± 0.04 mm (0.008 ± 0.002 in)

Oil System	
Oil type	Honda 4-stroke or an equivalent (SE or SF)
Recommended oil	SAE 10W-30
Oil capacity	0.55 l (0.58 US.qt.)

Ignition System	
Ignition timing	20° B.T.D.C.
Spark plug	NGK: BPR6ES
Spark plug gap	0.7-0.8 mm (0.028-0.031 in)
Primary ignition coil resistance	1.0-1.2 kΩ

Secondary ignition coil resistance	10.6-12.8 kΩ
Ignition coil air gap	0.2-0.6 mm (0.008-0.024 in)

Carburetor	
Main jet	#68
Float height	9.2 mm (0.36 in)
Pilot screw opening	1-3/4 turns out