

SAFETY DATA SHEET

FIXT Brake and Parts Cleaner

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name FIXT Brake and Parts Cleaner

Product number FX081105 FX081106 RFX08112

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses PC35 Washing and cleaning products

1.3. Details of the supplier of the safety data sheet

Supplier Seymour Road
Nuneaton
Warwickshire
CV11 4LB

02476 322 196 (T)
02476 322 117 (F)
info@fixtconsumables.com

1.4. Emergency telephone number

Emergency telephone 02476 322 196

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 2 - H411

Human health Gas or vapour in high concentrations may irritate the respiratory system.

Environmental The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Physicochemical Vapours may form explosive mixtures with air.

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

FIXT Brake and Parts Cleaner

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P273 Avoid release to the environment.</p> <p>P501 Dispose of contents/ container in accordance with local regulations.</p> <p>P403 Store in a well-ventilated place.</p> <p>P301 IF SWALLOWED:</p> <p>P315 Get immediate medical advice/ attention.</p> <p>P280 Wear protective gloves.</p> <p>P102 Keep out of reach of children.</p> <p>P262 Do not get in eyes, on skin, or on clothing.</p>
Supplemental label information	RCH002b For professional users only.
Contains	HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, PROPAN-2-OL
Detergent labelling	≥ 30% aliphatic hydrocarbons, < 5% perfumes, Contains d-LIMONENE

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			60-100%
CAS number: —	EC number: 921-024-6	REACH registration number: 01-2119475514-35	
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			

PROPAN-2-OL			5-10%
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 01-2119457558-25	
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336			

FIXT Brake and Parts Cleaner

HEXANE-norm			<1%
CAS number: 110-54-3	EC number: 203-777-6	REACH registration number: 01-2119480412-44	
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361f STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			

TURPENTINE, OIL			<1%
CAS number: 8006-64-2	EC number: 232-350-7	REACH registration number: 01-2119502456-45	
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			

ETHYL ACETATE			<1%
CAS number: 141-78-6	EC number: 205-500-4	REACH registration number: 01-2119475103-46	
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336			

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air at once.
Inhalation	In case of inhalation of spray mist: Move person into fresh air and keep at rest. Remove affected person from source of contamination. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. If in doubt, get medical attention promptly.
Ingestion	Immediately rinse mouth and provide fresh air. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	Wash skin thoroughly with soap and water. Remove contaminated clothing immediately and wash skin with soap and water.

FIXT Brake and Parts Cleaner

Eye contact Important! Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Foam. Dry chemicals. Water spray. Carbon dioxide (CO₂).

5.2. Special hazards arising from the substance or mixture

Specific hazards In case of fire, toxic gases may be formed.

Hazardous combustion products Highly flammable gases or vapours. During fire, toxic gases (CO, CO₂) are formed. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

5.3. Advice for firefighters

Protective actions during firefighting Use water to keep fire exposed containers cool and disperse vapours. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Water spray may be used to flush spills away from exposures and dilute spills to non-flammable mixtures. Use water spray to reduce vapours.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of dust and contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. Provide ventilation and confine spill. Do not allow runoff to sewer.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. Use good earthing procedures when decanting from container.

7.2. Conditions for safe storage, including any incompatibilities

FIXT Brake and Parts Cleaner

Storage precautions Flammable/combustible materials. Keep away from oxidising materials, heat and flames. Store at moderate temperatures in dry, well ventilated area. Keep away from heat, sparks and open flame.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Long-term exposure limit (8-hour TWA): WEL 1200 mg/m³

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

HEXANE-norm

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m³

TURPENTINE, OIL

Long-term exposure limit (8-hour TWA): WEL 100 ppm 566 mg/m³

Short-term exposure limit (15-minute): WEL 150 ppm 850 mg/m³

ETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 200 ppm

Short-term exposure limit (15-minute): WEL 400 ppm

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

PROPAN-2-OL (CAS: 67-63-0)

DNEL	Industry - Dermal; Long term systemic effects: 888 mg/kg/day
	Industry - Inhalation; Long term systemic effects: 500 mg/m ³
	Consumer - Dermal; Long term systemic effects: 319 mg/kg/day
	Consumer - Dermal; Long term systemic effects: 26 mg/kg/day
	Consumer - Inhalation; Long term systemic effects: 89 mg/m ³
PNEC	- Fresh water; 140.9 mg/l
	- Marine water; 140.9 mg/l
	- Intermittent release; 140.9 mg/l
	- Sediment (Freshwater); 552 mg/kg
	- Sediment (Marinewater); 552 mg/kg
	- STP; 2251 mg/l
	- Soil; 28 mg/kg

8.2. Exposure controls

Appropriate engineering controls Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of vapours.

Personal protection When using do not smoke

Eye/face protection Wear approved safety goggles.

FIXT Brake and Parts Cleaner

Hand protection	Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.
Hygiene measures	Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.
Respiratory protection	No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Colourless.
Odour	Hydrocarbons. Lemon.
Melting point	-95°C
Initial boiling point and range	56°C
Flash point	-18°C CC (Closed Cup)
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 2.5% Upper flammable/explosive limit: 13%
Relative density	0.722 @ °C
Auto-ignition temperature	540°C
Comments	Information given is applicable to the major ingredient.

9.2. Other information

Other information	Not available.
Volatile organic compound	This product contains a maximum VOC content of 850 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Stable at normal ambient temperatures and when used as recommended.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Does not decompose when used and stored as recommended.
---	---

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with oxidisers or reducing agents.
----------------------------	--

10.5. Incompatible materials

Materials to avoid	Keep away from oxidising materials, heat and flames.
---------------------------	--

10.6. Hazardous decomposition products

FIXT Brake and Parts Cleaner

Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours.
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation	Vapours may cause headache, fatigue, dizziness and nausea. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Ingestion	Harmful: may cause lung damage if swallowed.
Skin contact	Irritating to skin. Prolonged contact may cause redness, irritation and dry skin.
Eye contact	Irritating to eyes. Repeated exposure may cause chronic eye irritation.
Acute and chronic health hazards	Contents may cause lung damage if swallowed. Aspiration into the lungs may cause chemical pneumonitis. Irritating to eyes. Irritating to skin.
Route of exposure	Ingestion Inhalation
Target organs	Respiratory system, lungs

SECTION 12: Ecological Information

Ecotoxicity	The product contains a substance which may have hazardous effects on the environment.
--------------------	---

12.1. Toxicity

Toxicity	Not available.
-----------------	----------------

12.2. Persistence and degradability

Persistence and degradability	Not available.
--------------------------------------	----------------

12.3. Bioaccumulative potential

Bioaccumulative potential	Not available.
----------------------------------	----------------

12.4. Mobility in soil

Mobility	Not known.
-----------------	------------

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	Not available.
---	----------------

12.6. Other adverse effects

Other adverse effects	Not available.
------------------------------	----------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

SECTION 14: Transport information

General	Packs of 1L or less are not regulated under the limited quantities provisions .
----------------	---

14.1. UN number

UN No. (ADR/RID)	1993
UN No. (IMDG)	1993

FIXT Brake and Parts Cleaner

UN No. (ICAO) 1993

UN No. (ADN) 1993

14.2. UN proper shipping name

Proper shipping name (ADR/RID) FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, PROPAN-2-OL)

Proper shipping name (IMDG) FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, PROPAN-2-OL)

Proper shipping name (ICAO) FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, PROPAN-2-OL)

Proper shipping name (ADN) FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, PROPAN-2-OL)

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID label 3

IMDG class 3

ICAO class/division 3

Transport labels



14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ICAO packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-E, S-E

Emergency Action Code •3YE

Hazard Identification Number (ADR/RID) 33

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

FIXT Brake and Parts Cleaner

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	EH40/2005 Workplace exposure limits. The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended). The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].
EU legislation	Commission Regulation (EU) No 453/2010 of 20 May 2010.
Guidance	Workplace Exposure Limits EH40. Approved Classification and Labelling Guide (Sixth edition) L131. Safety Data Sheets for Substances and Preparations. British Aerosol Manufacturers Code of Practice 7th. Edition 1999

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	17/11/2017
Revision	3
SDS number	12424
Hazard statements in full	H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.