

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **FIXT Leak Detector**

FX081129 Product number

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Leak Detector

1.3. Details of the supplier of the safety data sheet

Supplier Seymour Road

> Nuneaton Warwickshire **CV11 4LB**

02476 322 196 (T) 02476 322 117 (F)

info@fixtconsumables.com

1.4. Emergency telephone number

02476 322 196 **Emergency telephone**

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Aerosol 3 - H229

Health hazards Eye Irrit. 2 - H319

Environmental hazards Not Classified

Human health Gas or vapour is harmful on prolonged exposure or in high concentrations. In high

> concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this

container is dangerous and can be fatal.

Environmental This product does not contain substances which are harmful to aquatic organisms or which

may cause long term effects to the aquatic environment

Physicochemical Aerosol containers can explode when heated, due to excessive pressure build-up.

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H229 Pressurised container: may burst if heated

H319 Causes serious eye irritation.

FIXT Leak Detector

Precautionary statements P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe vapour/spray.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

SODIUM LAURYL SARCOSINATE 1-5%

CAS number: 137-16-6 EC number: 205-281-5 REACH registration number: 01-

2119527780-39

Classification Classification (67/548/EEC or 1999/45/EC)

Acute Tox. 2 - H330 T;R23. Xi;R38,R41.

Skin Irrit. 2 - H315 Eye Dam. 1 - H318

Sodium Benzoate <1%

CAS number: 532-32-1 EC number: 208-534-8 REACH registration number: 01-

2119460683-35

Classification Classification (67/548/EEC or 1999/45/EC)

Eye Irrit. 2 - H319 Xi;R36.

SODIUM NITRITE <1%

CAS number: 7632-00-0 EC number: 231-555-9 REACH registration number: 01-

2119471836-27

M factor (Acute) = 1

Classification Classification (67/548/EEC or 1999/45/EC)

Ox. Sol. 3 - H272 O;R8 T;R25 N;R50

Acute Tox. 3 - H301 Eye Irrit. 2 - H319 Aquatic Acute 1 - H400

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air at once.

Inhalation If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing.

Ingestion Rinse mouth thoroughly with water. Do not induce vomiting.

FIXT Leak Detector

Skin contact Use suitable lotion to moisturise skin.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue

to rinse.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Containers can burst violently or explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Protective actions during

firefighting

Warn firefighters that aerosols are involved. Containers close to fire should be removed or

cooled with water.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Not considered to be a significant hazard due to the small quantities used.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Do not spray near a naked flame or any

incandescent material.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well

ventilated area. Pressurized container: protect from sunlight and do not expose to

temperatures exceeding 50°C. Do not pierce or burn, even after use.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

FIXT Leak Detector

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Sodium Benzoate

Long-term exposure limit (8-hour TWA): WEL 6.3 mg/m³

SODIUM NITRITE

Long-term exposure limit (8-hour TWA): No std.

WEL = Workplace Exposure Limit

8.2. Exposure controls

Appropriate engineering

controls

Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any

occupational exposure limits for the product or ingredients.

Personal protection When using do not smoke.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. The following protection should be worn: Chemical splash goggles.

Hand protection Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant,

impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough

time of the glove material.

Other skin and body

protection

Not relevant

Hygiene measures Wash hands after handling. Wash promptly if skin becomes contaminated. Wash hands at the

end of each work shift and before eating, smoking and using the toilet. Use appropriate skin

cream to prevent drying of skin.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour N/A

Odour No characteristic odour.

Flash point >100°C

Upper/lower flammability or

explosive limits

:

Relative density 1.0 @ 20°C

Solubility(ies) Soluble in water.

Comments Information given is applicable to the major ingredient.

9.2. Other information

Other information Not available.

Volatile organic compound This product contains a maximum VOC content of 0 g/l.

SECTION 10: Stability and reactivity

FIXT Leak Detector

10.1. Reactivity

Reactivity Stable at normal ambient temperatures and when used as recommended.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Does not decompose when used and stored as recommended.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Keep away from oxidising materials, heat and flames.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or

vapours

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 100,000.0

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 65.18904824

Inhalation May cause respiratory system irritation.

Ingestion No specific health hazards known.

Skin contact Skin irritation should not occur when used as recommended. Repeated exposure may cause

skin dryness or cracking.

Eye contact Vapour or spray in the eyes may cause irritation and smarting.

Acute and chronic health

hazards

Because of the product's quantity and composition, the health hazard is regarded as low. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause

headache, fatigue, dizziness and nausea.

Route of entry Inhalation

Target organs No specific target organs known.

Medical symptoms No specific symptoms noted, but this chemical may still have adverse health impact, either in

general or on certain individuals.

SECTION 12: Ecological Information

EcotoxicityNo negative effects on the aquatic environment are known. The product is not expected to be

toxic to aquatic organisms.

12.1. Toxicity

Toxicity Not available.

FIXT Leak Detector

12.2. Persistence and degradability

Persistence and degradability Not available.

12.3. Bioaccumulative potential

Bioaccumulative potential Not available.

12.4. Mobility in soil

Mobility Not known.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

Not available.

assessment

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Do not puncture or incinerate, even when empty.

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

SECTION 14: Transport information

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR

and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported

as Limited Quantities. Aerosols not so packed and labelled must show the following.

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper shipping name

AEROSOLS

(ADR/RID)

Proper shipping name

(IMDG)

AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.2

ADR/RID label 2.2

IMDG class 2.2

ICAO class/division 2.2

FIXT Leak Detector

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-D, S-U

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

EU legislation Commission Regulation (EU) No 453/2010 of 20 May 2010.

Guidance Workplace Exposure Limits EH40.

CHIP for everyone HSG228.

Safety Data Sheets for Substances and Preparations.

Approved Classification and Labelling Guide (Sixth edition) L131. British Aerosol Manufacturers Code of Practice 7th. Edition 1999

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments Supplemental information added.

Revision date 21/10/2015

Revision 2

SDS number 12439

SDS status Approved.

Risk phrases in full Not classified.

R23 Toxic by inhalation. R25 Toxic if swallowed. R38 Irritating to skin.

R41 Risk of serious damage to eyes. R50 Very toxic to aquatic organisms.

R8 Contact with combustible material may cause fire.

FIXT Leak Detector

Hazard statements in full H229 Pressurised container: may burst if heated

H272 May intensify fire; oxidiser.

H301 Toxic if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.