

SECTION 1: Identification of the substance/mixture and of the company/undertaking		
1.1. Product identifier		
Product name	FIXT Glass & Mirror Cleaner	
Product number	FX 081207	
1.2. Relevant identified uses of the substance or mixture and uses advised against		
Identified uses	Window glass cleaner.	
1.3. Details of the supplier of the	ne safety data sheet	
Supplier	Seymour Road Nuneaton	
	Warwickshire	
	CV11 4LB	
	02476 322 196 (T)	
	02476 322 117 (F) info@fixtconsumables.com	
	C	
1.4. Emergency telephone num		
Emergency telephone	02476 322 196	
SECTION 2: Hazards identification	ation	
2.1. Classification of the substa	ance or mixture	
Physical hazards	Aerosol 1 - H222, H229	
Health hazards	Not Classified	
Environmental hazards	Not Classified	
Classification (67/548/EEC or 1999/45/EC)	F+;R12.	
Human health	Gas or vapour is harmful on prolonged exposure or in high concentrations. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.	
Environmental	This product does not contain substances which are harmful to aquatic organisms or which may cause long term effects to the aquatic environment	
Physicochemical	Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.	
2.2. Label elements		
Pictogram		

Signal word

Danger

Hazard statements	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated
Precautionary statements	 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P102 Keep out of reach of children. P501 Dispose of contents/container in accordance with local regulations. P260 Do not breathe vapour/spray. P271 Use only outdoors or in a well-ventilated area.
Detergent labelling	< 5% aliphatic hydrocarbons,< 5% perfumes

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures			
1-METHOXY-2-PROPANOL			1-5%
CAS number: 107-98-2	EC number: 203-539-1	REACH registration number: 01- 2119457435-35	
Classification	Classifica	tion (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 R67	· · · · · ·	
Acute Tox. 4 - H312			
STOT SE 3 - H336			
PETROLEUM GASES, LIQUEFIED); PETROLEUM GAS		1-5%
CAS number: 68476-85-7	EC number: 270-704-2		
Classification	Classifica	tion (67/548/EEC or 1999/45/EC)	
Flam. Gas 1 - H220	F+;R12 C	arc. Cat. 1;R45 Muta. Cat. 2;R46	
Press. Gas, Liquefied - H280			
PROPAN-2-OL			1-5%
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 01-	
		2119457558-25	
Classification	Classifica	tion (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	F;R11 Xi;	R36 R67	
Eye Irrit. 2 - H319			
STOT SE 3 - H336			

SODIUM NITRITE		<1'
CAS number: 7632-00-0	EC number: 231-555-9	REACH registration number: 01- 2119471836-27
M factor (Acute) = 1		
Classification	Classifi	cation (67/548/EEC or 1999/45/EC)
Ox. Sol. 3 - H272	O;R8 T;	;R25 N;R50
Acute Tox. 3 - H301		
Eye Irrit. 2 - H319		
Aquatic Acute 1 - H400		
Hydrocarbons C11-C13 Isoa	lkanes, <2% aromatics	<1'
CAS number: 90622-58-5	EC number: 920-901-0	REACH registration number: 01- 2119456810-40
Classification	Classifi	cation (67/548/EEC or 1999/45/EC)
Asp. Tox. 1 - H304	Xn;R65	
The Full Text for all R-Phrase	s and Hazard Statements are Displayed ir	a Section 16
SECTION 4: First aid measure		
4.1. Description of first aid me		
General information	Move affected person to fresh air at once.	
Inhalation	keep warm and at rest in a position con	as follows. Move affected person to fresh air and affortable for breathing. If breathing stops, provide on warm and at rest. Get medical attention
Ingestion	Rinse mouth thoroughly with water. Do	not induce vomiting. Get medical attention.
Skin contact	Remove contaminated clothing immedia	ately and wash skin with soap and water.
Eye contact	Rinse immediately with plenty of water. apart. Continue to rinse for at least 15 n	Remove any contact lenses and open eyelids wide ninutes and get medical attention.
4.2. Most important symptoms	s and effects, both acute and delayed	
General information	The severity of the symptoms described length of exposure.	d will vary dependent on the concentration and the
4.3. Indication of any immedia	te medical attention and special treatmen	it needed
Notes for the doctor	Treat symptomatically.	
SECTION 5: Firefighting measure	sures	
5.1. Extinguishing media		
Suitable extinguishing media	Extinguish with foam, carbon dioxide, d	ry powder or water fog.
5.2. Special hazards arising fr	om the substance or mixture	
Specific hazards	may spread near ground and travel a co	mixtures with air. Vapours are heavier than air and onsiderable distance to a source of ignition and flash explode when heated, due to excessive pressure bui

5.3. Advice for firefighters

Protective actions during firefighting	Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved.		
SECTION 6: Accidental release	SECTION 6: Accidental release measures		
6.1. Personal precautions, pro	tective equipment and emergency procedures		
Personal precautions	Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of vapours.		
6.2. Environmental precaution	<u>s</u>		
Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material.		
6.3. Methods and material for	containment and cleaning up		
Methods for cleaning up	Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion.		
6.4. Reference to other section	ns		
Reference to other sections	For personal protection, see Section 8. For waste disposal, see Section 13.		
SECTION 7: Handling and sto	rage		
7.1. Precautions for safe hand	lling		
Usage precautions	Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Do not spray on a naked flame or any incandescent material.		
7.2. Conditions for safe storag	e, including any incompatibilities		
Storage precautions	Extremely flammable. Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.		
7.3. Specific end use(s)			
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.		
SECTION 8: Exposure Contro	Is/personal protection		
8.1. Control parameters Occupational exposure limits			

1-METHOXY-2-PROPANOL

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 375 mg/m3(Sk) Short-term exposure limit (15-minute): WEL 150 ppm(Sk) 560 mg/m3(Sk)

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³ Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³ Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

SODIUM NITRITE

Long-term exposure limit (8-hour TWA): No std.

Hydrocarbons C11-C13 Isoalkanes, <2% aromatics

Long-term exposure limit (8-hour TWA): SUP 177 ppm 1200 mg/m³ WEL = Workplace Exposure Limit

Ingredient comments	WEL = Workplace Exposure Limits
	1-METHOXY-2-PROPANOL (CAS: 107-98-2)
DNEL	Industry - Inhalation; Short term local effects: 553.5 mg/m ³ Industry - Dermal; Long term systemic effects: 369 mg/m ³ Industry - Inhalation; Long term systemic effects: 369 mg/m ³ Consumer - Dermal; Long term systemic effects: 18.1 mg/kg/day Consumer - Inhalation; Long term systemic effects: 43.9 mg/m ³ Consumer - Oral; Long term systemic effects: 3.3 mg/kg/day
PNEC	 Fresh water; 10 mg/l Marine water; 1 mg/l STP; 100 mg/l Sediment (Freshwater); 41.6 mg/kg Sediment (Marinewater); 4.17 mg/l Soil; 2.47 mg/kg Intermittent release; 100 mg/l
	PROPAN-2-OL (CAS: 67-63-0)
DNEL	Industry - Dermal; Long term systemic effects: 888 mg/kg/day Industry - Inhalation; Long term systemic effects: 500 mg/m³ Consumer - Dermal; Long term systemic effects: 319 mg/kg/day Consumer - Dermal; Long term systemic effects: 26 mg/kg/day Consumer - Inhalation; Long term systemic effects: 89 mg/m³
PNEC	- Fresh water; 140.9 mg/l - Marine water; 140.9 mg/l - Intermittent release; 140.9 mg/l - Sediment (Freshwater); 552 mg/kg - Sediment (Marinewater); 552 mg/kg - STP; 2251 mg/l - Soil; 28 mg/kg
8.2. Exposure controls	
Appropriate engineering controls	Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.
Personal protection	When using do not smoke.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.
Hand protection	Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.
Hygiene measures	Wash hands after handling. Wash promptly if skin becomes contaminated. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin.

Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn.
SECTION 9: Physical and Ch	emical Properties
9.1. Information on basic phys	sical and chemical properties
Appearance	Aerosol.
Colour	White/off-white.
Odour	Organic solvents.
Initial boiling point and range	-40 to -2°C @ 1013 hPa
Flash point	<-40°C
Upper/lower flammability or explosive limits	Lower : 1.8% - Upper 9.5%
Vapour pressure	ca. 590 to 1760 kPa @ 45°C
Vapour density	ca. 1.5 at 15°C
Partition coefficient	log Pow: ca. 2.3 to 2.8
Auto-ignition temperature	410-580°C
Comments	Information given is applicable to the major ingredient.
9.2. Other information	
Other information	Not available.
Volatile organic compound	This product contains a maximum VOC content of 328 g/l.
SECTION 10: Stability and rea	activity
10.1. Reactivity	
Reactivity	Stable at normal ambient temperatures and when used as recommended.
10.2. Chemical stability	
Stability	Avoid the following conditions: Heat, sparks, flames.
10.3. Possibility of hazardous	reactions
Possibility of hazardous reactions	Does not decompose when used and stored as recommended.
10.4. Conditions to avoid	
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.
10.5. Incompatible materials	
Materials to avoid	Keep away from oxidising materials, heat and flames.
10.6. Hazardous decomposition	on products
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours.
SECTION 11: Toxicological information	

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg)	100,000.0	
General information	Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.	
Inhalation	In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Unconsciousness, possibly death.	
Skin contact	Skin irritation should not occur when used as recommended. Repeated exposure may cause skin dryness or cracking.	
Eye contact	Vapour or spray in the eyes may cause irritation and smarting.	
Acute and chronic health hazards	Arrhythmia (deviation from normal heart beat). In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.	
Route of entry	Inhalation	
Target organs	Central nervous system Respiratory system, lungs	
Medical symptoms	Arrhythmia (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness.	
SECTION 12: Ecological Information		
Ecotoxicity	No negative effects on the aquatic environment are known. The product is not expected to be	

No negative effects on the aquatic environment are known. The product is not expected to be toxic to aquatic organisms.

12.1. Toxicity

Toxicity Not available.

12.2. Persistence and degradability

Persistence and degradability Not available.

12.3. Bioaccumulative potential

Bioaccumulative potential Not available. Partition coefficient log Pow: ca. 2.3 to 2.8

Not known.

12.4. Mobility in soil

Mobility

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB Not available. assessment

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Do not puncture or incinerate, even when empty.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated because of the risk of an explosion.

SECTION 14: Transport information

General	This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following.
14.1. UN number	
UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
14.2. UN proper shipping nam	e
Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS
14.3. Transport hazard class(e	<u>es)</u>
ADR/RID class	2.1
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
Transport labels	
14.4. Packing group	
Not applicable.	
14.5. Environmental hazards	
Environmentally hazardous su No.	bstance/marine pollutant
14.6. Special precautions for u	Iser
EmS	F-D, S-U
Tunnel restriction code	(D)
14.7. Transport in bulk accordi	ing to Annex II of MARPOL73/78 and the IBC Code
Transport in bulk according to	Not applicable.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

Torn Galoty, noalth and G	
National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Commission Regulation (EU) No 453/2010 of 20 May 2010.
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131. British Aerosol Manufacturers Code of Practice 7th. Edition 1999

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No chemical safety assessn	nent has been carried out.
SECTION 16: Other informa	ition
Revision comments	Supplemental information added.
Revision date	11/08/2015
Revision	3
SDS number	12402
SDS status	Approved.
Risk phrases in full	 R10 Flammable. R11 Highly flammable. R12 Extremely flammable. R25 Toxic if swallowed. R36 Irritating to eyes. R50 Very toxic to aquatic organisms. R67 Vapours may cause drowsiness and dizziness. R8 Contact with combustible material may cause fire.
Hazard statements in full	 H220 Extremely flammable gas. H222 Extremely flammable aerosol. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated H229 Pressurised container: may burst if heated H272 May intensify fire; oxidiser. H301 Toxic if swallowed. H301 Toxic if swallowed. H304 May be fatal if swallowed and enters airways. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H400 Very toxic to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.