

Page: 1

Compilation date: 08/04/2015

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: FIXT HQ SILICONE SEALANT BLACK

Product code: FX085532

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

## 1.3. Details of the supplier of the safety data sheet

Company name: Quest Consumables Ltd

Stock House Seymour Road Nuneaton Warwickshire CV11 4LB UK Tel: +44 (0)2476 322126 Fax: +44 (0) 2476 322117

Email: sales@questconsumables.com

# 1.4. Emergency telephone number

## Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; Eye Irrit. 2: H319; -: H229

Most important adverse effects: Pressurised container: May burst if heated. Causes skin irritation. Causes serious eye irritation.

## 2.2. Label elements

Label elements:

Hazard statements:	H229: Pressurised container: May burst if heated	
	H315: Causes skin irritation.	
	H319: Causes serious eye irritation.	
Hazard pictograms:	GHS07: Exclamation mark	



Signal words: Warning

Precautionary statements: P102: Keep out of reach of children.

# FIXT HQ SILICONE SEALANT BLACK

**Page:** 2

P103: Read label before use.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.P251: Do not pierce or burn, even after use.

P264: Wash contaminated skin thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P332+313: If skin irritation occurs: Get medical advice/attention.

P337+313: If eye irritation persists: Get medical advice/attention.

P362: Take off contaminated clothing.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

## 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

## 3.2. Mixtures

## Hazardous ingredients:

#### METHYLTRIACETOXYSILANE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	4253-34-3	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319;	1-10%
			STOT SE 3: H335	

#### 1,1,1,2-TETRAFLUORETHAN

212-377-0	811-97-2	Substance with a Community workplace exposure limit.	-	1-10%
PROPYLTRIACETOXYSILAN				

241-816-9	17865-07-5	-	Skin Corr. 1B: H314; -: EUH014	1-10%	

## Section 4: First aid measures

# 4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

# FIXT HQ SILICONE SEALANT BLACK

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

#### Section 5: Fire-fighting measures

### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

## 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

# Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

#### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Wash the spillage site with large amounts of water.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

# Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of dust in the air.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area.

7.3. Specific end use(s)

Specific end use(s): No data available.

## Section 8: Exposure controls/personal protection

## 8.1. Control parameters

# FIXT HQ SILICONE SEALANT BLACK

Page: 4

#### Hazardous ingredients:

## 1,1,1,2-TETRAFLUORETHAN

#### Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	4240 mg/m3	-	-	-

**Respirable dust** 

#### **DNEL/PNEC** Values

DNEL / PNEC No data available.

8.2. Exposure controls

Respiratory protection: Respiratory protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

## Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State:	Liquid	
Colour:	Black	
Odour:	Characteristic odour	
Evaporation rate:	No data available.	
Oxidising:	No data available.	
Solubility in water:	Not miscible	
Viscosity:	No data available.	
Boiling point/range°C:	>35 Melting point/range°C:	No data available.
Flammability limits %: lower:	No data available. upper:	No data available.
Flash point°C:	>93 Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available. Vapour pressure:	No data available.
Relative density:	1.08 pH:	No data available.
VOC g/I:	No data available.	

9.2. Other information

Other information: No data available.

#### Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

# FIXT HQ SILICONE SEALANT BLACK

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat.

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## **10.6. Hazardous decomposition products**

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

## 11.1. Information on toxicological effects

#### Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

## Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

#### 12.2. Persistence and degradability

## Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

## 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

# FIXT HQ SILICONE SEALANT BLACK

# Section 13: Disposal considerations

#### 13.1. Waste treatment methods

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## **Section 14: Transport information**

Transport class: This product does not require a classification for transport.

# Section 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# 15.2. Chemical Safety Assessment

# Section 16: Other information

## Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3: EUH014: Reacts violently with water.	
	H229: Pressurised container: May burst if heated
	H314: Causes severe skin burns and eye damage.
	H315: Causes skin irritation.
	H319: Causes serious eye irritation.
	H335: May cause respiratory irritation.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.