



**SAFETY DATA SHEET**  
**FIXT HQ SILICONE SEALANT RED**

Issued: 01/06/2012  
Revision No: 1

**Section 1. Identification of the substance/mixture and the company/undertaking**

**1.1 Product identifier**

**Product name:** FIXT HQ SILICONE SEALANT RED

**Product code:** FX085533

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** One component temperature resistant silicone sealing for high temperature application

**1.3 Details of the supplier and the safety data sheet**

**Company name:** Quest Consumables Ltd

Stock House

Seymour Road

Nuneaton

Warwickshire

CV11 4LB UK

**Tel:** +44 (0) 2476 322126

**Fax:** +44 (0) 24476 322117

**Email:** [sales@questconsumables.com](mailto:sales@questconsumables.com)

**1.4 Emergency telephone number**

**Section 2. Hazards Identification**

**2.1 Classification of the substance or mixture**

**Classification under CHIP:** This does not meet the criteria for classification as dangerous in accordance with Directive 1999/45/EC.

**Most important adverse effects:**

**2.2 Label elements**

**Label elements under CHIP:** Observe the general safety regulations when handling chemicals.

**Safety phrases:** S24/25: Avoid contact with skin and eyes.

S36/39: Wear suitable protective clothing and eye / face protection.

**Precautionary phrases:** Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C.

Do not pierce or burn, even after use.

**2.3 Other hazards**

**PBT:** This substance is not identified as a PBT substance.

**Section 3. Composition/information on ingredients**

**3.2 Mixtures**

**SAFETY DATA SHEET**  
**FIXT HQ SILICONE SEALANT RED**

**Hazardous ingredients:**

METHYLSILANETRIYL TRIACETATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
224-221-9	4253-34-3	C: R14	Skin corr.1B: H314	<2.5%

PROPYLTRIACETOXSILAN

EINECS	CAS	CHIP Classification	CLP Classification	Percent
241-816-9	17865-07-5	C: R34, R14, Xn: R22	Skin corr.1B: H314	<2.5%

1,1,1,2-TETRAFLUORETHAN

EINECS	CAS	CHIP Classification	CLP Classification	Percent
212-377-0	811-97-2	-	Press.Gas: H280	<2.5%

**Section 4: First aid measures**

**4.1 Description of first aid measures**

- Skin contact:** Clean with water and soap. Remove clothes. If skin irritation continues, consult a doctor.
- Eye contact:** Rinse opened eye immediately for several minutes under running water. Remove contact lenses, if present and easy to do. Continue rinsing. Then consult a doctor.
- Ingestion:** Rinse out mouth and then drink plenty of water if person is conscious. If symptoms persist consult a doctor.
- Inhalation:** Take affected persons into fresh air and keep quiet. Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation. Keep patient warm.

**4.2 Most important symptoms and effects, both acute and delayed**

**Delayed/Immediate effects:** No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

**Immediate/special treatment:** Symptomatic treatment (decontamination, vital bodily function).

**Section 5: Fire fighting measures**

**5.1 Extinguishing media**

**Extinguishing media:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray.

**5.2 Special hazards arising from the substance or mixture**

**Exposure hazards:** Carbon monoxide, carbon dioxide, hazardous fumes.

**5.3 Advice for fire-fighters**

**Advice for fire-fighters:** Wear a self-contained respiratory protective device. Cool endangered receptacles with water spray and remove it out of emergency area if possible. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

# SAFETY DATA SHEET

## FIXT HQ SILICONE SEALANT RED

### Section 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

**Personal precautions:** The usual precautions for handling construction chemicals are observed. Wear protective equipment. Ensure adequate ventilation.

#### 6.2 Environmental precautions

**Environmental precautions:** Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.

#### 6.3 Methods and material for containment and cleaning up

**Clean-up precautions:** Allow to solidify. Pick up mechanically. Dispose contaminated material as waste according to item 13.

#### 6.4 Reference to other sections

**Reference to other sections:** No dangerous substances are released. See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

### Section 7: Handling and storage

#### 7.1 Precautions for safe handling

**Handling requirements:** No special measures required. Do not eat, drink or smoke when using this product. Avoid contact with eyes and skin. Use only in well ventilated areas.

#### 7.2 Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool place in dry conditions. Store only in the original receptacle. Keep away from temperatures below 10 °C and above 40 °C as well as from direct sun light. Observe official regulations on storing packaging with pressurized containers.

**Suitable packaging:** Must only be kept in original packaging.

#### 7.3 Specific end use(s):

**Specific end use(s):** Temperature resistant silicone

### Section 8: Exposure controls/personal protection

#### 8.1 Control parameters:

<b>Workplace exposure limits:</b>	<b>64-19-7 acetic acid</b>	
	IOELV (European Union)	25 mg/m <sup>3</sup> , 10 ml/m <sup>3</sup>
	<b>811-97-2 1,1,1,2-Tetrafluorethan</b>	
	WEL	4,240 mg/m <sup>3</sup> , 1 000 ppm Long-term value
	<b><u>DNEL</u></b>	
	<b>64-19-7 acetic acid</b>	
	Inhalativ wrks, short, local:	25mg/m <sup>3</sup>
	wrks, long, local:	25mg/m <sup>3</sup>
	cons, short, local:	25mg/m <sup>3</sup>
	cons, long, local:	25mg/m <sup>3</sup>
	<b>811-97-2 1,1,1,2-Tetrafluorethan</b>	
	Inhalativ wrks, long, syst:	13,936mg/m <sup>3</sup>
	cons, long, syst:	2,476mg/m <sup>3</sup>
	<b><u>PNEC</u></b>	
	<b>64-19-7 acetic acid</b>	

# SAFETY DATA SHEET

## FIXT HQ SILICONE SEALANT RED

STP:	85,0 mg/l
intermittent release:	30,58 mg/l
sediment (fresh water):	11,36 mg/(kg sediment dw)
fresh water:	3,058 mg/l
sediment (marine water):	1,136 mg/(kg sediment dw)
soil:	0,47 mg/l
marine water:	0,3058mg/l

### 811-97-2 1,1,1,2-Tetrafluorethan

STP:	73,0 mg/l
intermittent release:	1,0 mg/l
fresh water:	0,1 mg/l
sediment (fresh water):	0,75 mg/(kg sediment dw)
marine water:	0,01 mg/l
soil:	No exposition expected.
Oral	No potential for bioaccumulation.

## 8.2 Exposure controls:

**General measures:** Give workers information about the harmful nature of the chemical mixture. Provide them with training on handling chemicals safely and what to do if something goes wrong. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. The usual precautionary measures are to be adhered to when handling chemicals.

**Respiratory protection:** Not necessary if room is well-ventilated. In other cases use respiratory filter device, e.g. EN 14387 type.

**Hand protection:** Impervious gloves. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation. EN 374-3 is recommended.

**Eye protection:** Goggles of EN 166 type are recommended during refilling.

**Skin protection:** Protective work clothing according EN 340, and EN ISO 20345.

## Section 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties:

<b>State:</b>	Paste-like
<b>Colour:</b>	Red
<b>Odour:</b>	Characteristic
<b>Solubility in water:</b>	Not miscible or difficult to mix.
<b>Kinematic viscosity:</b>	Not determined
<b>Viscosity test method:</b>	Not determined
<b>Boiling point/range °C:</b>	Not determined
<b>Melting point/range °C:</b>	Not determined
<b>Flash point °C:</b>	> 100 °C
<b>Relative density:</b>	1.08
<b>Solids content:</b>	99.9%

### 9.2 Other information

**Other information:** Not applicable.

## Section 10: Stability and reactivity

### 10.1 Reactivity

**Reactivity:** No decomposition if used according to specifications.

# SAFETY DATA SHEET

## FIXT HQ SILICONE SEALANT RED

### 10.2 Chemical stability

**Chemical stability:** No further relevant information available.

### 10.3 Possibility of hazardous reactions

**Hazardous reactions:** No dangerous reactions known.

### 10.4 Conditions to avoid

**Conditions to avoid:** No further relevant information available.

### 10.5 Incompatible materials

**Materials to avoid:** No further relevant information available.

### 10.6 Hazardous decomposition products

**Haz. decomp. products:** No dangerous decomposition products occur when handling in accordance with the rules.

## Section 11: Toxicological information

### 11.1 Information on toxicological effects

**Toxicity values:** 4253-34-3 **methylsilanetriyl triacetate**  
Oral LD50 1,600mg/kg (rat)

### Symptoms / routes of exposure

**Skin contact:** No irritant effect on the skin.

**Eye contact:** No irritant effect on the eyes.

**Sensitization:** No sensitization possible through skin contact.

**Additional toxicological information:** The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

**CMR effects:** No CMR effects known.

## Section 12: Ecological information

### 12.1 Toxicity

**Ecotoxicity values:** No further relevant information available.

### 12.2 Persistence and degradability

**Persistence and degradability:** No further relevant information available.

### 12.3 Bioaccumulation potential

**Bioaccumulative potential:** No further relevant information available.

### 12.4 Mobility in soil

**Mobility:** No further relevant information available.

### 12.5 Results of PBT and vPvB assessment

**PBT identification:** Not applicable.

**SAFETY DATA SHEET**  
**FIXT HQ SILICONE SEALANT RED**

**12.6 Other adverse effects**

**Other adverse effects:** Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water. Do not allow product to reach ground water, water course or sewage system, even in small quantities. According to our experience the product is not toxic for fishes after curing, if used properly.

**Section 13: Disposal considerations**

**13.1 Waste treatment methods**

**Recommendation:** Must not be disposed together with household waste. Do not allow product to reach sewage system.

**European waste catalogue:**

08 00 00 WASTE FROM MFSU OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS  
08 04 00 waste from MFSU of adhesives and sealants (including waterproofing products)  
08 04 09\* waste adhesive and sealants containing organic solvents or other dangerous substances

---

15 00 00 WASTE PACKAGING, ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED  
15 01 00 packaging (including separately collected municipal packaging waste)  
15 01 04 metallic packaging

---

16 00 00 WASTES NOT OTHERWISE SPECIFIED IN THE LIST  
16 05 00 gases in pressure containers and discarded chemicals  
16 05 04\* ases in pressure containers (including halons) containing dangerous substances

**Section 14: Transport information**

**14.1 UN number**

**UN number:** ADR, IMDG, IATA UN1950

**14.2 UN Proper shipping name**

**Shipping name:** ADR 1950 AEROSOLS  
IMDG AEROSOLS  
IATA AEROSOLS, non-flammable

**14.3 Transport hazard class(es)**

**Transport class:** ADR Class 2 5A Gases  
Label 2.2

IMDG, IATA Class 2.2  
Label 2.2

**14.4 Packing group**

**Packing group:** ADR, IMDG, IATA Void

**14.5 Environmental hazards**

**Marine pollutant:** No

**EMS Number:** F-D, S-U

**14.6 Special precautions for user**

ADR

# SAFETY DATA SHEET

## FIXT HQ SILICONE SEALANT RED

**Limited quantities (LQ):** 1L  
**Transport category:** 3  
**Tunnel restriction code:** E  
**Special precautions Warning:** Gases  
**UN "Model Regulation":** UN1950, AEROSOLS, 2.2

### Section 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/regulation specific for the substance or mixture

**Labelling according to EU guidelines:** Observe the general safety regulations when handling chemicals. The product is not subject to identification regulations under EU Directives and the Ordinance on Hazardous Materials (German GefStoffV).

**Special labelling of certain preparations:** Safety data sheet available for professional user on request.

**National regulations:** –

**Information about limitation of use:** Employment restrictions concerning juveniles according to Council Directive 2007/30/EC must be observed. Employment restrictions concerning pregnant and lactating women according to Council Directive 92/85/EEC must be observed.

**Breakdown regulations:** Critical quantity values according to the regulations on accidents should be adhered to.

**Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

#### 15.2 Chemical Safety assessment

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### Section 16: Other information

#### 16.1 Other information

**Other information:** This safety data sheet is prepared in accordance with commission Regulation (EU) No 453/2010.

**Phrases used in s.2 and 3:**

- H280 Contains gas under pressure; may explode if heated.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- R14 Reacts violently with water.
- R22 Harmful if swallowed.
- R34 Causes burns.
- S3 Keep in a cool place

**Legal disclaimer:** The above information is believed to be correct, but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.