



12/24 VOLT DERV PUMP/HOSE KIT
Model No: J1224/KITC

Thank you for purchasing a Lumeter product. Manufactured to a high standard, this product if used according to these instructions and properly maintained will give you trouble free performance.



Important

PLEASE READ THESE INSTRUCTIONS CAREFULLY, NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNING AND CAUTIONS. USE THIS PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT WAS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE, OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. RETAIN THESE INSTRUCTIONS FOR FUTURE USE.

1 Please read instructions

Please follow instructions below before starting the pump.

Warning: This pump is only suitable for use with Diesel/Gas Oil.

It must not be used to dispense Petrol, Kerosene, Flammable or Water Based Liquids

- IMPORTANT! All threads must be tight and sealed with PTFE tape
- IMPORTANT! Ensure that the inlet and outlet hose assemblies are connected to the correct chamber ports. (Arrow in pump casting shows flow direction)
- Do not run the pump dry - only operate when the chamber is wet.
- Keep the outlet open when priming to enable air to be expelled.
- Never stop or start pump with the crocodile clips - Use the switch.
- Switch off pump within two minutes of the nozzle being closed.
- Maximum run time a) 12 volt = 30 minutes b) 24 volt = 30 minutes
- Disconnect the crocodile clips and remove from the battery when not in use.
- IP55 Protection: By-pass valve/maximum pressure = 3 bar

2 Pump Kit Set-Up

- Connect outlet hose with the gun

Running Time:

12 volt = 30 minutes

24 volt = 30 minutes

Please use this product with care and for the purpose to which it is intended. Failure to do so may cause damage, or personal injury and will invalidate the warranty.