



MORRIS
LUBRICANTS

Product Information:

VERSIMAX[®] HD14 10W-30 **ADVANCED DIESEL ENGINE OIL**

Description

Versimax[®] HD14 10W-30 is a mid-SAPS heavy duty diesel engine oil, manufactured from Group II and Group III base fluids. This product contains an advanced additive package formulated to provide the utmost protection when operating in very severe conditions with extended drain intervals.

Versimax[®] HD14 10W-30 has been developed for use in diesel engines fitted with exhaust gas re-circulation (EGR), selective catalytic reduction (SCR – Adblue) NOx reduction systems, diesel oxidation catalysts (DOC) and diesel particulate filters (DPF). Versimax HD14 10W-30 has been designed to cope with increased levels of bio-fuel and their effect in the engine.

Applications

Versimax[®] HD14 10W-30 is designed for use in Euro 5 / Euro 6, Interim Tier 4 / Stage 3B / Tier 4 and Stage 4 / Stage 5 diesel engines, where any of the performance levels shown below are specified. Market sectors include: commercial vehicles, coaches, buses, off-highway and agricultural equipment, etc.

Performance Levels

API CK-4
ACEA E9
CAT ECF-3
Cummins CES 20086
Detroit Diesel DFS Oil Specification 93K222
MAN 3775
Mercedes Benz 228.31
Deutz DQC III-18 LA
MTU Type 2.1
Ford I71-F1

Approvals

Volvo VDS-4.5
Mack EO-S-4.5
Renault VI RLD-3

Physical Characteristics

Density @ 15°C	0.872
Kinematic Viscosity at 100°C, cSt.	12.1
Kinematic Viscosity at 40°C, cSt.	85.84
Viscosity Index	138
Flash Point (closed) °C	204
TBN, mg/KOH/g	9.4
Sulphated Ash, %wt.	1.0
Pour Point, °C	-36

Figures based on average production values.

Part No.s: VMF025, VMF205

(TDS Versimax[®] HD14 10W-30 – 260122 Issue 6)

